



rot15

1/14/2024

608-238-6001 [ TEL ]

greg@infinityturbine.com [ Email ]

Infinity Turbine  
LLC

ROT15 Radial Outflow Turbine ROT ORC



This webpage QR code

### Structured Data

```

<script type="application/ld+json">
  {
    "@context": "http://schema.org",
    "@graph": [
      {
        "@type": "Organization",
        "@id": "https://infinityturbine.com/#organization",
        "name": "Infinity Turbine LLC",
        "url": "https://infinityturbine.com",
        "sameAs": [
          "https://www.youtube.com/channel/UCsobpvy0xqc13uvhA71Cv4w",
          "https://x.com/InfinityTurbine",
          "https://www.instagram.com/infinityturbine/",
          "telephone": "608-238-6001",
          "email": "greg@infinityturbine.com",
          "logo": "https://infinityturbine.com/logo.png"
        ]
      },
      {
        "@type": "WebSite",
        "@id": "https://infinityturbine.com",
        "url": "https://infinityturbine.com",
        "name": "ROT15 Radial Outflow Turbine ROT ORC",
        "description": "Company Name: Infinity Turbine LLCProduct: ROT 15 Turbine Generator AssemblyWorking Fluid: Refrigerants, water, and CO2Working Pressure: Less than 300 psi. Certification: Experimental. Not ASME certified as is.Drawings Provided: As is. Machine: ORC and ROT Radial Outflow Turbine SystemIndustry: EnergyApplications: Waste heat to power, utilities, server farms, bitcoin mining, hot geothermal.High Technology Uses: Converting waste heat to power.Machine Features: One moving part.Machine Runs On: Air, and some refrigerants, such as R245. Can be converted to a CO2 turbine with proper engineering enhancements with materials and seals which can withstand ASME coded materials and construction for 2,000 psi or more.Real World Testing: This turbine has been built and tested with air (15-100 psi) and R245fa under pressure (300 psi or less). Experimental.Seals: Gruvlok or Victaulic couplings which allow turbine to be mounted to a common shaft generator within one assembly.Other Applications: Can be run as an expander or extractor.Bearings: Uses motor bearings.Systems: This has been used with a 15 kW and 30 kW system. Two together can run a IT50 or 50 kW. Modular systems can be interconnected."
      },
      {
        "@type": "NewsArticle",
        "mainEntityOfPage": {
          "@type": "WebPage",
          "@id": "https://infinityturbine.com/rot15.html",
          "headline": "ROT15 Radial Outflow Turbine ROT ORC",
          "image": "https://infinityturbine.com/images/20181104-infinity-turbine-rot15-rotor-assembled.jpg",
          "datePublished": "2024-01-14T08:00:00+08:00",
          "dateModified": "2024-01-14T09:20:00+08:00",
          "author": {
            "@type": "Organization",
            "name": "Infinity Turbine LLC",
            "url": "https://infinityturbine.com"
          },
          "publisher": {
            "@type": "Organization",
            "name": "Infinity Turbine LLC",
            "logo": {
              "@type": "ImageObject",
              "url": "https://infinityturbine.com/logo.png"
            }
          }
        }
      }
    ]
  }
}</script>

```

Company Name: Infinity Turbine LLC  
 Product: ROT 15 Turbine Generator Assembly  
 Working Fluid: Refrigerants, water, and CO2  
 Working Pressure: Less than 300 psi.  
 Certification: Experimental. Not ASME certified as is.  
 Drawings Provided: As is.  
 Machine: ORC and ROT Radial Outflow Turbine System  
 Industry: Energy  
 Applications: Waste heat to power, utilities, server farms, bitcoin mining, hot geothermal.  
 High Technology Uses: Converting waste heat to power.  
 Machine Features: One moving part.  
 Machine Runs On: Air, and some refrigerants, such as R245. Can be converted to a CO2 turbine with proper engineering enhancements with materials and seals which can withstand ASME coded materials and construction for 2,000 psi or more.  
 Real World Testing: This turbine has been built and tested with air (15-100 psi) and R245fa under pressure (300 psi or less). Experimental.  
 Seals: Gruvlok or Victaulic couplings which allow turbine to be mounted to a common shaft generator within one assembly.  
 Other Applications: Can be run as an expander or extractor.  
 Bearings: Uses motor bearings.  
 Systems: This has been used with a 15 kW and 30 kW system. Two together can run a IT50 or 50 kW. Modular systems can be interconnected.

PDF Version of the webpage (first pages)

<https://infinityturbine.com/rot15.html>

## ROT15 Radial Outflow Turbine AC Induction Generator Plans and Blueprints

Pricing: Please refer to price list or email Infinity.

IT10 Revenue based on gross sales or grid savings, not including cost of acquiring waste heat flow or pumps.

Revenue from IT10 (24 hours x 365 days per year x 10 kWh = 87,600 kWh per year):

at \$.20 per kWh = \$17,520 USD per year

at \$.40 per kWh = \$35,040 USD per year

at \$.80 per kWh = \$70,080 USD per year

1/14/2024

## ROT Turbine Design

The ROT15 Radial Outflow Turbine has a 15 inch diameter. The ROT15 can drive (depending on pressure) a 10 to 50 kW generator. If an induction AC motor generator is used, you will need a grid tie device. This design is for 300 psi or lower working pressures. With enhanced material design, or vessel strength, and generator designs which can withstand higher temperatures and pressures, you can use higher pressures. The blueprints offered, are only for the turbine (the generator you purchase separately) and assembly of the turbine generator. System plans for a complete ORC Organic Rankine Cycle System are sold separately, and include the evaporator/condenser heat exchangers, feedpump, PLC Control, piping, valves, VFD, frame, and system components.

## Turbine Design

The turbine design is unique in that it uses the generator shaft and bearings for support, and a simple pipe with Gruklok or Victaulic couplings to seal in the pressure.

The flat end plates (discs) are easily waterjet or machined out of aluminum or stainless steel. If you are using CO2 or water/steam for the working fluid, we suggest more durable bearings that will tolerate the pressurized environment.

You can also use a shaft seal to isolate the turbine section, and put the DC or AC generator outside, which does not require any special bearing lubrication that is tolerant to the inside turbine working fluid.

## Blueprints

While we are focusing on larger designs for our systems, we are offering these blueprints for sale as is, which include a unlimited build license.

We may offer updates from time-to-time, and support is not included with the price.

## **Plans Download:**

The plans include images of each component in (jpg/png) and .pdf views.

The machine ready files include dwg, dxf, xt and we can provide other files on request from our AutoDesk suite of Cad/Cam software.

The files are provided by download.

The license is for the turbine blueprints only, and does not include any support (optional).

If you would like system blueprints (bill of materials, heat exchangers, pump/motor, frame, piping, etc.) for our Supercritical CO2 or standard R245fa, or R134a, please contact us.

1/14/2024

1/14/2024











---

---

---

---

---

---

